Suction capacity



Power consumption



Time to fill a tank of 40dm³ capacity



Max. r.p.m. for continuous duty



TECHNICAL DATA:

Number of cylinders	1	
Cylinder diameter	75	mm
Piston stroke	36	mm
Total piston displacement	159	cm^3
Mass	10	kg
Working pressure	1000	kPa
Max. pressure for short time duty	1200	kPa
Max. allowable temp. of compressed air	+220	°C
Cooling by inflation of air, with the speed of the stream min.	4	m/s
Lubrication forced circulation, splash lubrication min. pressure of oil	300±200	kPa
(The pressure drop down is allowed to min. during the idle running of the heated up engine)	60	kPa

SYMBOLS DESCRIPTION:

0 – suction connection
2 – discharge connection
81 – lubricating oil inlet
82 – lubricating oil outlet and crankcase breathing
Numeral signs according to International Standard ISO-6786
T – rating plate
* – max. angular deflection of the compressor







NOTE! The above characteristics are for open-inlet-valve control system at minimum cooling requirements and at ambient temperature +20°C

DEFINITIONS:

CC=CT+CL – period of average operating cycle

$UC=\frac{CT}{CC}\times 100\%$ – percent ratio of compressor full load operating time in average operating cycle(also called percent duty cycle)

CL – compressor no-load operating time (exhaust to the atmosphere)

CT – compressor full load operating time

Accuracy of the cone: 1:5 AT 9 PN-77/M-02136

Replace: 411 141 816 0 up to 10 bar
411 141 818 0 up to 10 bar

OFFER DRAWING

Konstr.	K.Malinowski		10.09.2003
Normaliz.	A.Walnicki		
Sprawdził	W.Lesiak		
Zatwierdził	W.Lesiak		

FABRYKA OSPRZĘTU SAMOCHODOWEGO POLMO-Łódź S.A. Dział Konstrukcji

Podziałka	Nazwa
1:2.5	Compressor 601.09.913